




CSG/CAL - aluframe with sliding lids

CSG/CAL - aluframe with sliding lids



Reliable freezers, that just do the job

Reliable freezers, that just do t




The CAL comes with sliding solid lids



A lock is easily mounted



Special basket scoop-ice-cream available



he job




At first sight it may look like a traditional freezer for ice cream. However, we have built in something important - namely a very high quality and reliability. This means that the customer can just plug it in and forget about it for years to come - it will simply do its job.

Furthermore, our CSG/CAL-programme is probably the widest on the market. It stretches from the compact CSG 18 - suitable for small outlets - to roomy CSG 73, suitable even for supermarkets. And the many sizes in between ensure that there is something for any need.

The CSG/CAL-range can be fitted with a number of different features and is available in all climate classes.

For many years our quality has proven itself all over the world - why don't you try it too?

s for
am are



The rigid aluminium-profile makes a strong frame



An easily readable digital thermometer is optional



Technical data

| | | CSG 18 | CSG 22 | CSG 35 | CSG 45 | CSG 53 | CSG 61 | CSG 73 | CAL 18 | CAL 22 | CAL 35 | CAL 45 | CAL 53 | CAL 61 |
|----------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Gross volume | litres | 170 | 217 | 349 | 450 | 530 | 611 | 700 | 163 | 209 | 337 | 435 | 513 | 590 |
| Net volume | litres | 146 | 188 | 304 | 393 | 441 | 509 | 622 | 146 | 188 | 304 | 393 | 441 | 509 |
| Gross volume | cu.ft. | 6,1 | 7,7 | 12,5 | 16,1 | 18,9 | 21,8 | 25,0 | 5,8 | 7,5 | 12,1 | 15,5 | 18,3 | 21,1 |
| Net volume | cu.ft. | 5,2 | 6,7 | 10,9 | 14,0 | 15,8 | 18,2 | 22,2 | 5,2 | 6,7 | 10,9 | 14,0 | 15,8 | 18,2 |
| A | mm | 624 | 724 | 1054 | 1304 | 1504 | 1704 | 1800 | 624 | 724 | 1054 | 1304 | 1504 | 1704 |
| B | mm | 624 | 654 | 654 | 654 | 654 | 654 | 690 | 624 | 654 | 654 | 654 | 654 | 654 |
| C | mm | 916 | 916 | 916 | 916 | 916 | 916 | 916 | 916 | 916 | 916 | 916 | 916 | 916 |
| D | mm | 780 | 780 | 780 | 780 | 780 | 780 | 780 | 780 | 780 | 780 | 780 | 780 | 780 |
| E | mm | 510 | 606 | 936 | 1186 | 1386 | 1586 | 1686 | 510 | 606 | 936 | 1186 | 1386 | 1586 |
| F | mm | 310 | 406 | 736 | 986 | 1186 | 1386 | 1486 | 310 | 406 | 736 | 986 | 1186 | 1386 |
| G | mm | 510 | 536 | 536 | 536 | 536 | 536 | 576 | 510 | 536 | 536 | 536 | 536 | 536 |
| H | mm | 750 | 750 | 750 | 750 | 750 | 750 | 750 | 726 | 726 | 726 | 726 | 726 | 726 |
| J | mm | 475 | 500 | 500 | 500 | 500 | 500 | 500 | 476 | 495 | 495 | 495 | 495 | 495 |
| L | mm | 846 | 846 | 846 | 846 | 846 | 846 | 846 | 846 | 846 | 846 | 846 | 846 | 846 |
| Castors | | + | + | + | + | + | + | + | + | + | + | + | + | + |
| External thermometer | | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. |
| Lock | | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. |
| Baskets | | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. |
| Dividers | | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. | opt. |

Subject to alterations. The technical specifications should be taken as a guidance.

