

# PRO FREEZER

## LOW TEMPERATURE FREEZER

(-60 °C)



Rack system and boxes available

### FEATURES:

- SINGLE COMPRESSOR/LOW ENERGY
- LESS SPACE REQUIRED
- LOW PRICE
- DIGITAL CONTROLLER
- ENVIRONMENTAL FREINDLY REFRIGERANT
- REMOTE ALARM (OPTION)
- TEMPERATURE RECORDER (OPTION)



QUALITY SYSTEM AND ENVIRONMENTAL MANAGEMENT SYSTEM  
DS/EN ISO 9001  
DS/EN ISO 14001



Latest update 22.06.2010



**TECHNICAL SPECIFICATIONS:**

|                               |        | PRO 11       | PRO 21       | PRO 31       | PRO 41       | PRO 60       |
|-------------------------------|--------|--------------|--------------|--------------|--------------|--------------|
| Ambient temperature           | °C     | +10° to +30° | +10° to +30° | +10° to +30° | +10° to +30° | +10° to +30° |
| Net. Volume                   | Litres | 130          | 230          | 300          | 360          | 485          |
| Height with 50 mm castors     | mm     | 920          | 920          | 920          | 920          | 920          |
| Height with open lid          | mm     | 1620         | 1620         | 1620         | 1620         | 1620         |
| Width                         | mm     | 720          | 1050         | 1300         | 1500         | 1700         |
| Insulations Thickness         | mm     | 100          | 100          | 100          | 100          | 100          |
| Depth excl. Handle and hinges | mm     | 730          | 730          | 730          | 730          | 730          |
| Power consumption at + 25°C   | Watts  | 330          | 410          | 560          | 610          | 610          |
| Fuse                          | A      | 10           | 10           | 10           | 10           | 10           |
| Temperature Range             | °C     | -30° to -60° | -30° to -60° | -30° to -60° | -30° to -60° | -30° to -60° |
| Noise level                   | dBa    | < 51         | < 51         | < 51         | < 51         | < 51         |
| Weight                        | kg     | 53           | 68           | 78           | 89           | 95           |